

DATREX Lifering Throw Rope

DX0100M 100 ft (30.5 m)

DX0100M

TYPE

U.S.C.G./SOLAS compliant lifering ropebags

USES

Presented in a high visibility orange bag with the rope perfectly coiled for immediate and continual use. The bag features a handle for control whenever in use and also doubles as a hanger on the lifering bracket. Constructed of marine grade components and contains 100 feet of 3/8" floating hollow braided polypropylene.

FEATURES

- Meet or exceeds USCG requirements under 46 CFR 180.70
- Rope Bag with 100ft of rope (30.5m)
- 3/8in hollow braided polypropylene
- Yellow rope
- Floating rope
- Minimum tensile strength of 3/8" hollow braid polypropylene rope is 1250 pounds

SPECIFICATIONS

ITEM NO.	DX0100M	
USE	For regular lifering installations	
LENGTH OF ROPE	100ft (30.5 m)	
COLOR OF ROPE	Yellow	
DIAMETER OF ROPE	3/8" (9.5 mm)	
TENSILE STRENGTH	1250 lbs (567 kg)	
WEIGHT	3 lbs (1.36 kg)	
DIMENSIONS	16 x 7 x 4 in (40 x 18 x 10 cm)	
MOLD RESISTANT	Yes	
HARDWARE	Marine grade	
COLOR OF COVER	International Orange	
COVER	Coated heavy denier polyester shell fabric	



APPROVAL/COMPLIANCE

Meet or exceeds USCG requirements under 46 CFR 180.70



DATREX