

# DATREX Lifering Throw Rope

## DX0150M 150 ft (45.7 m)

DX0150M

### TYPE

U.S.C.G./SOLAS compliant lifering ropebags

### USES

Presented in a high visibility orange bag with the rope perfectly coiled for immediate and continual use. The bag features a handle for control whenever in use and also doubles as a hanger on the lifering bracket. Constructed of marine grade components and contains 150 feet of 3/8" floating hollow braided polypropylene.

### FEATURES

Meet or exceeds USCG requirements under 46 CFR 180.70

Rope Bag with 150ft of rope (45.7m)

3/8in hollow braided polypropylene with UV inhibitor

Yellow rope

Floating rope

Minimum tensile strength of 3/8" hollow braid polypropylene rope is 1250 pounds

### SPECIFICATIONS

ITEM NO.	DX0150M	
USE	For regular lifering installations	
LENGTH OF ROPE	150ft (45.7 m)	
COLOR OF ROPE	Yellow with UV inhibitor (tested to ISO 4892-2:2013)	
DIAMETER OF ROPE	3/8" (9.5 mm)	
TENSILE STRENGTH	1250 lbs (567 kg)	
WEIGHT	4 lbs (1.81 kg)	
DIMENSIONS	16 x 8.5 x 4 in (40 x 22 x 10 cm)	
MOLD RESISTANT	Yes	
HARDWARE	Marine grade	
COLOR OF COVER	International Orange	
COVER	Coated heavy denier polyester shell fabric	



### APPROVAL/COMPLIANCE

Meet or exceeds USCG requirements under 46 CFR 180.70 and SOLAS



...DATREX...