

30" LIFERING WITHOUT TAPE

DX0300D Bridgebuoy®

DX0300D

TYPE

Type IV U.S.C.G. 30" Lifering Without Reflective Tape

USES

Lifering buoy 30", 2.5 kg orange buoy without retro reflective tape for installations such as on lifeguard stations at beaches or pools, docks, board walks, buildings that are next to water and yachts not required to comply with SOLAS . All Datrex rings are molded from high impact linear low-density polyethylene for superior life expectancy in the most severe environments. U.S. Coast Guard approvals. * From the CFR 46, Small Passenger Vessels (under 100 gross tons) " A vessel of more than 7.9 meters (26 feet) in length, but not more than 19.8 meters (65 feet), must carry a minimum of one life buoy of not less than 610 millimeters (24 inches) in diameter". " A vessel of more than 19.8 meters (65 feet) in length must carry a minimum of three life buoys of not less than 610 millimeters diameter (24 inches) in diameter.

FEATURES

All Datrex rings are molded from high impact linear low-density polyethylene for superior life expectancy in the most severe environments. The encircling black, floating rope is replaceable.

SPECIFICATIONS

ITEM NO.	DX0300D	
USE	Recreational use on inland waterways	
SIZE	30" (76 cm)	
WEIGHT	5.5 lbs (2.5 kg)	
CLOSED CELL FOAM	Yes	
MOLD RESISTANT	Yes	
RETRO-REFLECTIVE	No	
COLOR	International Orange	
QUANTITY PER CASE	3 per case	
CASE DIMENSIONS	31 x 31 x 13 inches (63.5 x 63.5 x 25.4 cm)	
CASE WEIGHT	28 lbs (12.7 kg)	
QUANTITY PER PALLET	27 liferings	
PALLET DIMENSIONS	43 x 48 x 65 inches (102 x 122 x 140 cm)	
PALLET WEIGHT	252 lbs (114 kg)	
PALLET VOLUME	78 ft ³ (2.20 m ³)	



APPROVAL/COMPLIANCE

U.S.C.G. Approval No: 160.050/124/0



---DATREX---