



Datrex VSG Lifejackets Mk10

USCG/SOLAS - USCG Type I

- **A premium quality family of lifejackets** for the high seas which are designed and approved for the US Flag market and for users who require SOLAS/USCG approvals
- **Exceptionally comfortable** and will turn an unconscious person to a face-up position
- **High freeboard** for improved survivability in rough seas
- **Compact** design for efficient, foldable storage
- **High visibility;** bright orange fabric and fitted with SOLAS retro-reflective tape
- **Equipped** with lifting loop, buddy line and whistle
- **Attachment for lifejacket light** (light not included) – Alcares Jack A1-ALK preferred light!*
- **Transparent pocket** for muster information
- **Sized** for Adult Universal/Oversize/Child/Infant
- **Complies with SOLAS;** evaluated, tested and found to be in compliance with the IMO LSA Code (Res MSC. 48 (66)), Section 2.2 as amended through Res. MSC. 207(81), and IMO Res. MSC. 81(70) as amended through Res. MSC. 200(80).



The Alcares Lifejacket Light AL1000ALKAM LED, alkaline powered (providing full 60 months of shelf-life), non-hazardous and water activated. USCG/SOLAS/MED.





ITEM	SIZE	WEIGHT	USCG NUMBER	DIMENSIONS in inches
VSCG2050AM	UNIVERSAL/OVERSIZE	>43 KG / >95 LBS	160.155/209/0	26 x 4.4 x 16
VSCG2051CM	CHILD	15-43 KG / 33-95 LBS	160.155/210/0	20 x 3.5 x 13
VSCG2052IM	INFANT	<15 KG / <33 LBS	160.155/211/0	16 x 4.0 x 11

Alcares Lifebuoy Light with bracket SOLAS/MED – ALBL15H-ALKM

Water-activated Lifebuoy Light with flashing High-Intensity LED. Comes complete with sturdy bracket and lanyard for attachment to lifebuoy. The Alcares Lifebuoy Light will turn ON when submerged in water and automatically turn OFF when out of water.

ADVANTAGES OVER OTHER SOLAS/MED LIFEBOUY LIGHTS:

- Longer operational time, min 15 hours versus 2 for SOLAS/MED
- No Fire Hazard/No Disposal Cost/No Hazardous Lithium - Alkaline instead!
- Brighter thanks to the High-Intensity LED Flashing Light



- Shelf-Life: 5 years Alkaline / Sealed
- Water-activated and includes a "test button"
- Flash rate: 51/flushes/minute at min 2 candela
- Operational Life: More than 15 hours
- Drop tested to 72 meters
- Size light: 210 mm X 96 mm / 8.3" x 3.8"
- Size bracket 110 mm X 110 mm X 130 mm / 4.3" x 4.3" x 5.1"
- Approved according to SOLAS MED 96/98/EC, USCG approval pending